ALL

FLOOR PLAN NOTES

- I. INTERIOR WALL DIMENSIONS ARE FROM FACE OF STUD TO FACE OF STUD, DIMENSIONS TAKEN TO EXTERIOR EDGE OF THE BUILDING ARE MEASURED TO THE FACE OF SHEATHING. EXTERIOR WALLS ARE FLUSH WITH I'RIGID @ FOUNDATION WALL SEE TYP. WALL DETAIL.
- WINDOW SIZES INDICATED ON PLANS ARE NOTED BY ROUGH OPENING SIZES, REFER TO PLANS AND EXTERIOR ELEVATIONS FOR WINDOW TYPES.
- 3. DO NOT SCALE DRAWINGS, FOLLOW DIMENSIONS ONLY.
- 4. CONTRACTOR SHALL FIELD VERIFY ALL CABINET DIMENSIONS BEFORE FABRICATION.
- 5. ALL BATH AND TOILET AREA WALLS AND CEILINGS SHALL HAVE WATER RESISTANT GYPSUM BOARD.
- 6. ALL INTERIOR WALLS SHALL BE COVERED WITH 1/2" GYPSUM BOARD AND METAL CORNER REINFORCING. USE 5/8" GYPSUM BOARD ON CEILINGS.
- HANDRAILS SHALL BE MOUNTED 32"-34" ABOVE NOSING OF STAIRS. GUARDRAILS SHALL BE MOUNTED AT 36".
- 8. PROVIDE ACCESS TO ALL CONCEALED ATTIC SPACES.


FIRST FLOOR PLAN

Ш REMO Ш SWIR

500 S. CREEK RD

NORTHBAY,WI





GENESIS

4061 N. MAIN ST. SUITE 200 RACINE, WISCONSIN 53402 TEL. 262-752-1894 FAX . 262-752-1895 www. genesisarchitecture.com office@genesisarchitecture.com

6/20/07